

To Whom It May Concern:

Commission expires:

I hereby attest that Josh Sondrol is a Certified Intoxilyzer Quality Assurance Specialist for the Lake Havasu City Police Department.

I certify that the attached documentation of Standard Quality Assurance Procedures and/or Standard Calibration Check Procedure are full, true and correct copy of the original.

Signature

STATE OF ARIZONA	)				
	) ss				
COUNTY OF MOHAVE	)				
		1-41		,	
Subscribed and sworn to b	pefore me this	135	_ day of _	Octobeo	2000
by	Josh	Souch	ol		
NOTARY PUBLIC	<b>3</b>		_		
10-13-	2020				~
DATE			( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( )	LORI SCHNEPF lotary Public - Arizona Mohave County Commission # 558867	
Commission expires:	7/ 7-		My Co	mm. Expires Feb 26, 202	3

#### Area Code 928

Fax #'s Administration ...... 855-4884 Administration ...... 680-5430 Business Office ...... 855-1171 Business Office ...... 680-5431 Investigations ...... 855-5775 Investigations/Patrol ...... 680-5432 Patrol ...... 855-0515

2-24-23

Emergency ...... 9-1-1 Non-Emergency Dispatch/ ..... 855-4111 Havasu Silent Witness ...... 854-TIPS

E-mail: police@lhcaz.gov

WHI GOLD

Exhibit G-2. Standard Calibration Check Procedure. Intoxily.or Model 8000

# THIS PERFORM TERPARED IN RST AND ADDITED BY A 22 CO. TO BREAK STATE OF PUBLIC SAFLEY.

# STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHICK PROCEDURE

QA SPECIALIST J SOLDREL 187 AGENCY LNC PI DATE 5/23/19 TIME 06-17 INTOXILYZER SERIAL # 80-003355 LOCATION JAIC			
DATE 5/23/19 AGENCY [NC ]	)		
INTOXILYZER SERIAL # 80.003255			Maria de Caración
LOCATION JAIC	Account to the control of the contro	and the second second second second second second second	
standard alcohol grant a	. 1 700	<b>-</b>	manage worth within the
Pour a standard alcohol concentration solution  that a tight seal has been made. Turn on the simulator and allow temperature to reach 34° (  Intoxilyzer 8000 display reads "PUSH BUTTON TO STAPT".	olution .1()(	<u>)</u> AC.	
that a tight seal has been made. Turn on the simulator and allow temperature to reach 34° (  13 Go to the "Control Testing Mann".	nd assemble th	e simulatore	r
Intoxilyzer 8000 display reads "PUSH BUTTON TO START"  ENTER.  Air blank completed.	C ≠ 0.2° C	manarity.	Ensure
ENTER.  14. Air blank completed.	After selection	15 made ou	
7.5. Calibration cheek	•	is made pres	256
7.6. Air blank completed. Test results 0. O AC	•		
Remove printed record Attach the record to the completed checklist			
GNATURE () ATA 1100			
STATE TO STATE OF THE STATE OF			
S. Force No. 1. C. o. v.			
PG Fonn Exh G 건 (Rev 03-01)			
Historical Note  New Exhibit G-2 made by final rulemaking at 12 A.A.R. 1916, effective 9:00 a.m., May 18,	INTEXTUTER 89	35	
at 12 A.A.R. 1916, effective 9:00 a.m., May 18,	Location: CHAM	NE:_	91
	Semiai Number: Come wersion: :	83-003355 a.ac.xo	X
	35/23/2619	J195,4G	0 36: 47: 39
	Standard Lot#;	170171474	**********
	Last Changed Bu	r J. SOMOROL	4187
	JAS: J. SOMPROL		
	LAKE HAUASU CIT	A 50 H101	
	30003200 : 70		
	Operator: 3, so LAKE HAUASU (17	ADMOF 416.	
	Test	ş0.a.	~ 75 <u>5</u>
	Air Blank	d. 190	 06: 47: 3
	0.100 Cal Check	ē.:3:	06,47:5
	Air Slank	8.739	D6:48:2

Preventative Maintenance Performed -- Timer Reset Department of Public Safety - Alcohol Testing

#### Exhibit G-4. Standard Quality Assurance Procedure Intoxilyzer, Model 8000

#### THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104(A)

#### ARIZONA DEPARTMENT OF PUBLIC SAFETY

### STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

#### STANDARD QUALITY ASSURANCE PROCEDURE

QA SPECIALIST J SON DONG 187 AGENCY LUCPD			
DATE 5/23/19 TIME (265/2)			
INTOXILYZER SERIAL # 80 4003355 LOCATION JAIL			CONTRACTOR OF STREET
( 1. Display Reads "PUSH BUTTON TO START"			
DIAGNOSTIC TESTS			0
( \( \superstack 1\). Clock time check. ( \( \superstack 2\). Date check.	i i na salazi kulo Salazi i na fiziki Saniya kuttan ka	-	d
OPERATIONAL TESTS  ( 1. Alcohol-free subject test result 0. AC.	Othe Wersion, 6 08/00/2008	), 43 	) 16:51:39
( \( \sum_2 \). Error recognition logic system functioning.  Not a Successfully Completed Test Sequence printed ( \( \sum_3 \). Proper sample recognition system.	Engrano Lota Last Changed By.	79.7 0.3 79.7 0.3 0. 509.0402 #	
Not a Successfully Completed Test Sequence printed Deficient sample printed	1481 (N. \$04090) 1481 (N. \$04090) 1418 (44 48) (N.T.		
AC. Result 0. AC.	.pereton: U. EGA	***********	
Instrument is operating properly and accurately. YES NO		9 <u>5</u>	
COMMENTS	Subject: F2+0.75 1156: 1011. 0x38 Jenutrus 2013	it No. 111	
a /	15 Minute Jephik	**********	*es
SIGNATURE 187	Test:		
DPS Form Exh G-4 (Rev 05-01)  Historical Note	AVA Buark Duag catio Test Hindiank	222	36: \$2:\$ 36: 52:\$ 36: 53: 23
New Exhibit G-4 made by final rulemaking at 12 A.A.R. 1916, effective 9:00 a.m., Mag	Supression of the second of th		06: 53: 44 06: 54: . 2 36: 55: 40 96: 55: 51 36: 56: 3
京野党(日本展立 ) 新   日本   新展立   本書   日本   日本   のまましま   日本   日本   日本   日本   日本   日本   日本   日	amo 😓		
	Со	uccessf mpletec	1
ununununu V	?5t	Sequer	100

## Acizona Administrativo Code

Allen Star

Exhibit G-2. Standard Culibration Cheek Procedure, Invasilyan Model 8000

ARTHORN O'S TO THE PERSONNEL TO DEST IMPOSITE HE A STEEL WHICH HE IS ARTHORN AS THE BUSINESS OF THE STEEL ARTHORN AS A STEEL AR

PLANDARD QUALTIN ASSURANCE PROF. EDURGES. IN FOXILYZER MODEL 8000

SEASONARD CALIBRATION CHECK PROCEDURE

OA SPECIALIST SUMPER 187 AGENCY LNC PD  DATE SJ23 19 TIME ON DO  INTOXILYZER SERIAL # & COSSS LOCATION JAIL  (***I. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solved that a tight seal has been made. Turn on the simulator and allow temperature to reach 34° C.  1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solved that a tight seal has been made. Turn on the simulator and allow temperature to reach 34° C.  2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START"  ENTER.  (***J**Air blank completed.  (***J**Air blank comple	ition//	imulator E.	isure
SIGNATURE (Rev 05-01)  Historical Note  New Exhibit G-2 made by final rulemaking at 12 A.A.R. 1916, effective 9:00 a.m., May 18, 1	UMICALLIZER 830 Location: In4YM6 Senial Mumber: 8 Sone bension: 8 05/23/2019	EL 90-303355	<b>J</b>
	Standard Listk: i Last Shanged By:	J. SOMOROL :	#187
	UAT. 1 STAGAS. UHKE HAUAS. 0,79		
	Coenedon: U (56MCP3) #197 1445 HH1450 (1771)80		
	Test:	3 1.0.	
	Air Blank 0.100 Cal Check Air Élank	0.000 0.331 9.000	37: + 1: 25 37: : :: 46 37: : :2: :16

Preventative Maintenance Performed -- Timer Reset