LHCFD NFPA 704 Signage Requirements By Type of Hazardous Material



5003.5 Hazard Identification Signs: Unless otherwise exempted by the LHC *Fire Code Official (FCO)*, visible **hazard identification signs** as specified in **NFPA 704** for the specific material contained shall be placed on <u>stationary containers</u> and <u>aboveground tanks</u> and at <u>entrances to locations</u> where hazardous materials are <u>stored</u>, <u>dispensed</u>, <u>used or handled in quantities requiring a permit and at <u>specific entrances</u> and locations designated by the FCO. Where conflicts exist in regulations regarding threshold quantities signage, the most stringent requirements shall prevail.</u>

Type of Material	Class	Threshold Amount Exceeding	2012 IFC Sections
Combustible Liquids	(2) II/III-A	110 gallons	105.5.16
	(1) III-B	220 gallons	
Corrosive Materials			
Gases		200 cu. ft.	105.6.8
Liquids		55 gallons	105.6.20
Solids		1000 lbs.	105.6.20
Cryogenic Fluids			
Flammable		>1 gallon indoors / 60 gallons outdoors	105.6.10
Inert		60 gallons indoors / 500 gallons outdoors	105.6.10
Oxidizing		10 gallons indoors / 50 gallons outdoors	105.6.10
Physical or Health Hazards (Other)		Any Amount	105.6.10
Explosive Materials Fireworks		Any Amount	105.6.14
		Any Amount Any Amount	5601.1.3 & 5609
Pyrotechnic Materials Flammable Materials		Any Amount	
Gases	4&3 /2 /1	1,000 cu. ft. / 2,000 cu. ft. / 4,000 cu. ft.; @NTP	105.6.8
Liquids	1 403/2/1	1,000 cd. 1t. / 2,000 cd. 1t. / 4,000 cd. 1t., @NTF	105.6.16 &
Solids	4&3/2/1	500 lbs. / 1,000 lbs. / 2,000 lbs.	105.6.20
Highly Toxic Materials	700/2/1	000 103. / 1,000 103. / 2,000 103.	100.0.20
Gases		Any Amount	105.6.8
Liquids		Any Amount	105.6.20
Toxic Solids	1	Any Amount	105.6.20
Inert & Simple Asphyxiate		6,000 cu. ft. @ NTP	105.6.8
Compressed Gases		0,000 04.11. @ 1411	100.0.0
LP-Gas (Includes Propane)		50 cu. ft. in/out doors / 500 gallons (R-3 Occ's)	
= · · · · · · · · · · · · · · · · · · ·		1 cubic foot propane = 0.0278 gallons propane	
		1 gallon propane = 35.97 cubic feet propane	
Organic Peroxides		9, 1,	
Liquids / Solids			
Class I & II	I & II	Any Amount	105.6.20
Class III	III	1 gallon / 10 lbs.	105.6.20
Class IV	IV	2 gallons / 20 lbs.	105.6.20
Class V	V	Unlimited	
Oxidizing Materials			
Gases (Including Oxygen)		504 cu. ft. @ NTP	105.6.8
Liquids / Solids			
Class 4	4	Any Amount	105.6.20
Class 3	3	1 gallon / 10 lbs.	105.6.20
Class 2	2	10 gallons / 100 lbs.	105.6.20
Class 1	1	55 gallons / 500 lbs.	105.6.20
Pyrophoric Materials			
Gases, Liquids & Solids		Any Amount	105.6.20
Radioactive Materials		Any Amount	
Toxic Materials		Anna Anna anna	105.0.0
Gases		Any Amount	105.6.8
Liquids		10 gallons	105.6.20
Solids	1	100 lbs.	105.6.20
Unstable (Reactive) Materials			
Liquids / Solids / Gases		100 pounds / 10 sellers / 50 sec 51	105 6 20
Class 4 Class 3	4	100 pounds / 10 gallons/ 50 cu. Ft.	105.6.20
	3	100 pounds / 10 gallons/ 50 cu. Ft.	105.6.20
Class 2 Class 1	2	500 pounds / 55 gallons/ 1,000 cu. Ft. 500 pounds / 55 gallons/ 1,000 cu. Ft.	105.6.20 105.6.20
Water-Reactive Materials	 '	Joo pourius / 55 gailions/ 1,000 cu. Ft.	100.0.20
Liquids & Solids			
Class 3	3	Any Amount	105.6.20
Class 3 Class 2	2	5 gallons / 50 lbs.	105.6.20
Class 1	1	55 gallons / 500 lbs.	105.6.20
OIGOU I		Too ganono / ooo iba.	100.0.20

ARIZONA TIER TWO CHEMICAL REPORTING





Emergency Planning and Community Right-to-Know Act (EPCRA) Hazardous Chemical Inventory Reporting Requirements Per EPCRA §311-312

Facilities with chemicals in quantities that equal or exceed the following thresholds must report:

- For Gasoline (all grades combined) at a retail gas station, the threshold level is 75,000 gallons, if the tank(s) was stored entirely underground and was in compliance at all times during the preceding calendar year with all applicable Underground Storage Tank (UST) requirements at 40 CFR part 280 or requirements of the State UST program approved by the Agency under 40 CFR part 281.
- For Diesel Fuel (all grades combined) at a retail gas station, the threshold level is 100,000 gallons, if the tank(s) was stored entirely underground and the tank(s) was in compliance at all times during the preceding calendar year with all applicable UST requirements at 40 CFR part 280 or requirements of the State UST program approved by the Agency under 40 CFR part 281.
- For Extremely Hazardous Substances (EHSs)(40 CFR part 355 <u>Appendix A</u> and <u>Appendix B</u> (PDF)), either 500 pounds or the Threshold Planning Quantity (TPQ), whichever is lower.
- For **All Other Hazardous Chemicals**: 10,000 pounds

Facilities that need to submit MSDSs (or SDSs) or the list of hazardous chemicals under §311, also need to submit an Annual Inventory Report for the same chemicals (EPCRA §312). This Inventory Report must be submitted to the SERC, LEPC and LHCFD by March 1st of each year.

Arizona State Emergency Response Commission Contacts

Randall Matas, Deputy Director

Water Quality Division

Arizona Dept. of Environmental Quality

1110 West Washington Street

Phoenix, Arizona 85007

Phone: 602-771-2306 / 602-771-2306 Email: Randall Matas (<u>rgm@azdeq.gov</u>) Webpage: <u>https://azdeq.gov/AZSERC</u> NFPA 704 Standard System for the Identification of the Hazards of Materials for Emergency Response

NFPA 704 Signage Requirements

§5003.5.1 Markings. <u>Individual containers</u>, cartons or packages shall be conspicuously marked or labeled in an approved manner.

<u>Rooms or cabinets</u> containing compressed gases shall be conspicuously labeled: **COMPRESSED GAS**.

§5003.6 Signs. Required signs and markings shall not be obscured or removed, shall be in English or in symbols allowed by the IFC, shall be <u>durable</u>, and the <u>size</u>, color and lettering shall be approved.

Refer to your MSDS/SDS for the **specific hazard ratings** for the materials requiring NFPA 704 Hazard Identification.

The **size** of the placard or label is dependent on the distance at which the hazard ratings must be legible. The FCO will provide guidance on both the <u>size</u> of the hazard ratings, relative to the size of the placard/label, based on the <u>distance</u> at which the ratings are legible. For minimum standards, see below.

Distance at which hazard ratings are legible (size)	Minimum size of hazard ratings numbers required
Indoor Labels & Placards 8" x 8" minimum diamond	Use 3 inch Black numbers
Building Placards 15"x15" minimum diamond	Use 6 inch Black numbers

FIGURE 704 9.1 (c) Minimum Size of Numerals for Legibility at Distance.

