

To Whom It May Concern:

I hereby attest that Michael T. Maloy, Jr. is a Certified Intoxilyzer Quality Assurance Specialist for the Lake Havasu City Police Department.

I certify that the attached documentation of Standard Quality Assurance Procedures and/or Standard Calibration Check Procedure are full, true and correct copy of the original.

Area Code 928

REBECCA JOY DUTHIE Notary Public - Arizona Mohave County Commission # 574982 My Comm. Expires Dec 7, 2023

 Administration
 855-4884
 Fax #'s
 Emergency
 9-1-1

 Business Office
 855-1171
 Administration
 680-5430
 Non-Emergency Dispatch/
 855-4111

 Investigations
 855-5775
 Business Office
 680-5431
 Havasu Silent Witness
 854-TIPS

 Patrol
 855-0515
 Investigations/Patrol
 680-5432
 680-5432
 680-5432

E-mail: police@lhcaz.gov

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. MALOY #281 AGENCY LNCPD
DATE 01-17- 2021 TIME 0911
INTOXILYZER SERIAL # 80-003356 LOCATION SIEN 8
() 1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution OR
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
 2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START" 3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
4. Air blank completed. 5. Calibration check completed. Test results 0. 099 AC. 6. Air blank completed.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE Michael Maly # 281
DPS Form Exh G-2 (Rev 05-01)

Location: CHANNEL SIGN 8 Serial Number: 80-003356 Core Version: 8105.48

01/17/2021

09:11:51

Standard Lot#: 35019100A1

Last Changed By: M. MALOY JR #281

QAS: M. MALOY JR #281 LAKE HAVASU CITY PD

Operator: M. MALOY JR #281

LAKE HAVASU CITY PD

Test	g/210L	Time
Air Blank	0.000	09:12:25
0.100 Cal Check	0.099	09:12:46
Air Blank	0.000	09:13:16

Preventative Maintenance Performed -- Timer Reset

${\it EXHIBIT~G-4} \\ {\it THIS~REPORT~PREPARED~PURSUANT~TO~DUTY~IMPOSED~BY~A.A.C.~R13-10-104~(A)}$

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD QUALITY ASSURANCE PROCEDURE

QA SPECIALIST M. MALOY #281 AGENCY LHCPD
DATE 01-17- 2021 TIME 0915
INTOXILYZER SERIAL# 80-003356 LOCATION SIGN 8
(/) 1. Display Reads "PUSH BUTTON TO START"
DIAGNOSTIC TESTS () 1. Clock time check. () 2. Date check.
OPERATIONAL TESTS () 1. Alcohol-free subject test result 0. 600 AC. () 2. Error recognition logic system functioning. Not a Successfully Completed Test Sequence printed () 3. Proper sample recognition system. Not a Successfully Completed Test Sequence printed Deficient sample printed. () 4. Standard Calibration Check standard 0. 100 AC. Result 0. 097 AC. Instrument is operating properly and accurately. YES NO NO
COMMENTS
, , , , , , , , , , , , , , , , , , ,
SIGNATURE_MichaelMolog #VBI
DPS Form Exh G-4 (Rev 05-01)

Location: CHANNEL SIGN 8 Serial Number: 80-003356 Core Version: 8105.48

01/17/2021

09:15:29

Standard Lot#: 35019100A1
Last Changed By: M. MALOY JR #281

QAS: M. MALOY JR #281
LAKE HAVASU CITY PD

Operator: M. MALOY JR #281
LAKE HAVASU CITY PD

Subject: SQAP, TEST DOB: 01/01/2000

Sex: M

Weight: 200

15 Minute Deprivation Period? Yes

_Test	g/210L	Time
Air Blank	0.000	09:16:19
Diagnostic Test	Pass	09:16:54
Air Blank	0.000	09:17:21
0.100 Cal Check	0.099	09:17:42
Air Blank	0.000	09:18:11
Subject Test	0.000	09:18:36
Air Blank	ABT*	09:18:42
Air Blank	IPS**	09:18:50

^{*}Sequence Aborted

^{**}Improper Sample

Location: CHANNEL SIGN 8 Serial Number: 80-003356 Core Version: 8105.48

01/17/2021

09:19:36

Standard Lot#: 35019100A1 Last Changed By: M. MALOY JR	#281
QAS: M. MALOY JR LAKE HAVASU CITY PD	#281
Operator: M. MALOY JR LAKE HAVASU CITY PD	#281

Subject: SQAP, TEST DOB: 01/01/2000

Sex: M

Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	09:20:23
Diagnostic Test	Pass	09:20:59
Air Blank	0.000	09:21:26
0.100 Cal Check	0.099	09:21:47
Air Blank	0.000	09:22:16
Subject Test	0.000*	09:25:24
Air Blank	0.000	09:25:51
Air Blank	0.000	09:26:19
Subject Test	XXX**	09:26:33
Air Blank	RFI***	09:26:43

^{*}Deficient Sample

Begin new deprivation period

Not a Successfully Completed Test Sequence

^{**}Invalid Sample

^{***}RFI Detect

${\tt EXHIBIT~G-2}\\ {\tt THIS~REPORT~PREPARED~PURSUANT~TO~DUTY~IMPOSED~BY~A.A.C.~R13-10-104~(A)}$

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. MALOY # 281	_AGENCY_L/	1CPD
DATE 01-17- 2021	_TIME	0927
INTOXILYZER SERIAL # 8b-003356	LOCATION	SI 6 N B
(1. Ensure that gas tank is attached to instrument and	contains a standard	alcohol concentration solutionO.100 AC
Pour a standard alcohol concentration solution simulator. Ensure that a tight seal has been made. 0.2°C	AC, into	a clean dry simulator and assemble the ator and allow temperature to reach 34°C \pm
 2. Intoxilyzer 8000 display reads "PUSH BUTTON" 3. Go to the "Control Testing Menu". Select "D" for made press ENTER. 	dry control test or	"W" for wet control test. After selection is
4. Air blank completed. 5. Calibration check completed. Test results 0. 6. Air blank completed.		
7. Remove printed record. Attach the record to the c		
SIGNATURE	gr #281	
DPS Form Exh G-2 (Rev 05-01)		
	/	

Location: CHANNEL SIGN 8 Serial Number: 80-003356 Core Version: 8105.48

01/17/2021

09:27:53

Standard Lot#: 35019100A1

Last Changed By: M. MALOY JR #281

QAS: M. MALOY JR #281 LAKE HAVASU CITY PD

Operator: M. MALOY JR #281

LAKE HAVASU CITY PD

Test	g/210L	Time
Air Blank	0.000	09:28:23
0.100 Cal Check	0.097	09:28:44
Air Blank	0.000	09:29:13

Preventative Maintenance Performed -- Timer Reset