

To Whom It May Concern:

I hereby attest that Larry Allen, is a Certified Intoxilyzer Quality Assurance Specialist for the Lake Havasu City Police Department.

I certify that the attached documentation of Standard Quality Assurance Procedures and/or Standard Calibration Check Procedure are full, true and correct copy of the original.

Signature # Z51

Area Code 928

CARLA DUARTE Notary Public – Arizona Mohave County My Comm. Expires Mar 29, 2021

Administration	855-4884
Business Office	855-1171
Investigations	855-5775
Patrol	855-0515

Commission expires:

Fax #'s	
Administration	680-5430
Business Office	680-5431
Investigations/Patrol	680-5432

E-mail: police@lhcaz.gov

# EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A) $\,$

### ARIZONA DEPARTMENT OF PUBLIC SAFETY

### STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

### STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST L. ALLEN #251 AGENCY LHCPD
DATE 03-11-2020 TIME 0134
INTOXILYZER SERIAL # 80-003356 LOCATION LHC DD SIGN #8 CHANNET
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution OR
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
<ol> <li>Intoxilyzer 8000 display reads "PUSH BUTTON TO START"</li> <li>Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.</li> <li>Air blank completed.</li> </ol>
5. Calibration check completed. Test results 0. 097 AC. 6. Air blank completed. 7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE #251

DPS Form Exh G-2 (Rev 05-01)

#251

INTOXILYZER 8000

Location: CHANNEL SIGN 8 Serial Number: 80-003356 Core Version: 8105.48

03/11/2020 01:34:52

-----

Standard Lot#: 13518100A1

Last Changed By: J. SONDROL #187

QAS: L. ALLEN #251 LAKE HAVASU CITY PD

\_\_\_\_\_\_

Operator: L. ALLEN #251 LAKE HAVASU CITY PD

\_\_\_\_\_\_

Test	g/210L	Time
Air Blank	0.000	01:35:46
0.100 Cal Check	0.097	01:36:06
Air Blank	0.000	01:36:36

Preventative Maintenance Performed -- Timer Reset

## EXHIBIT G-4 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

### ARIZONA DEPARTMENT OF PUBLIC SAFETY

## STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

### STANDARD QUALITY ASSURANCE PROCEDURE

QA SPECIALIST L. ALLEN #251 AGENCY LHC PD
DATE 03-11-2020 TIME 0140
INTOXILYZER SERIAL # 80-003356 LOCATION LHC PS SIGN #8 CHANNE
( /) 1. Display Reads "PUSH BUTTON TO START"
DIAGNOSTIC TESTS  ( ) 1. Clock time check. ( ) 2. Date check.
OPERATIONAL TESTS  ( ) 1. Alcohol-free subject test result 0. OOO AC.  ( ) 2. Error recognition logic system functioning.  Not a Successfully Completed Test Sequence printed  ( ) 3. Proper sample recognition system.  Not a Successfully Completed Test Sequence printed  Deficient sample printed.  ( ) 4. Standard Calibration Check standard 0. AC. Result 0. O97 AC.  Instrument is operating properly and accurately. YES NO
COMMENTS
SIGNATURE #Z51  DPS Form Exh G-4 (Rev 05-01)

A 251

INTOXILYZER 8000

Location: CHANNEL SIGN 8 Serial Number: 80-003356 Core Version: 8105.48

03/11/2020 01:40:21

Standard Lot#: 13518100A1
Last Changed By: J. SONDROL #187

QAS: L. ALLEN #251
LAKE HAVASU CITY PD

Operator: L. ALLEN #251
LAKE HAVASU CITY PD

Subject: SQAP, TEST DOB: 01/01/1995

Sex: M Weight: 170

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	01:41:22
Diagnostic Test	Pass	01:41:57
Air Blank	0.000	01:42:25
0.100 Cal Check	0.097	01:42:45
Air Blank	0.000	01:43:15
Subject Test	0.000	01:43:40
Air Blank	ABT*	01:43:49
Air Blank	IPS**	01:43:57

<sup>\*</sup>Sequence Aborted

<sup>\*\*</sup>Improper Sample

INTOXILYZER 8000

Location: CHANNEL SIGN 8 Serial Number: 80-003356 Core Version: 8105.48

03/11/2020

01:44:28

Standard Lot#: 13518100A1
Last Changed By: J. SONDROL #187

QAS: L. ALLEN #251
LAKE HAVASU CITY PD

Operator: L. ALLEN #251
LAKE HAVASU CITY PD

Subject: SQAP, TEST DOB: 01/01/1995

Sex: M

Weight: 170

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	01:45:27
Diagnostic Test	Pass	01:46:02
Air Blank	0.000	01:46:30
0.100 Cal Check	0.098	01:46:50
Air Blank	0.000	01:47:20
Subject Test	0.000*	01:50:28
Air Blank	0.000	01:50:55
Air Blank	0.000	01:51:22
Subject Test	XXX**	01:51:44
Air Blank	RFI***	01:51:55

<sup>\*</sup>Deficient Sample

Begin new deprivation period

Not a Successfully Completed Test Sequence

<sup>\*\*</sup>Invalid Sample

<sup>\*\*\*</sup>RFI Detect

AZS1

## EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

### ARIZONA DEPARTMENT OF PUBLIC SAFETY

## STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

### STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST L. ALLEN # 7.51 AGENCY LHC PD
DATE 03-11-2020 TIME 0153
INTOXILYZER SERIAL # 80-003356 LOCATION LITC PD SIGN #8 CHANNEL
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution OR
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the
simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START"
3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
4. Air blank completed.
5. Calibration check completed. Test results 0. 097 AC.
6. Air blank completed.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE # Z51
DPS Form Exh G-2 (Rev 05-01)

INTOXILYZER 8000

Location: CHANNEL SIGN 8 Serial Number: 80-003356 Core Version: 8105.48

03/11/2020

01:53:51

\_\_\_\_\_\_

Standard Lot#: 13518100A1

Last Changed By: J. SONDROL #187

QAS: L. ALLEN #251 LAKE HAVASU CITY PD

-----

Operator: L. ALLEN #251 LAKE HAVASU CITY PD

\_\_\_\_\_\_

Test	g/210L	Time
	· · · ·	
Air Blank	0.000	01:54:23
0.100 Cal Check	0.097	01:54:44
Air Blank	0.000	01:55:13

Preventative Maintenance Performed -- Timer Reset t 251