

To Whom It May Concern:

I hereby attest that Michael T. Maloy, Jr. is a Certified Intoxilyzer Quality Assurance Specialist for the Lake Havasu City Police Department.

I certify that the attached documentation of Standard Quality Assurance Procedures and/or Standard Calibration Check Procedure are full, true and correct copy of the original.

STATE OF ARIZONA
) ss

COUNTY OF MOHAVE
)

Subscribed and sworn to before me this 19 day of May

2021 by Ashley Rue Bonds

NOTARY PUBLIC

5/19/2 |

DATE

Commission expires: May 29, 2021

Area Code 928

Administration 855-4884	Fax #'s	Emergency 9-1-1
Business Office 855-1171	Administration 680-5430	Non-Emergency Dispatch/ 855-4111
Investigations 855-5775	Business Office 680-5431	Havasu Silent Witness 854-TIPS
Patrol	Investigations/Patrol 680-5432	

E-mail: police@lhcaz.gov

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. MALOY #281 AG	ENCY LHCPD
DATE 05-19-2021 TIM	Æ 1700
INTOXILYZER SERIAL # 80-003355 LO	CATION JAIL
(1. Ensure that gas tank is attached to instrument and conta OR	tins a standard alcohol concentration solution 6.100 AC.
Pour a standard alcohol concentration solution simulator. Ensure that a tight seal has been made. Turn 0.2°C 2. Intoxilyzer 8000 display reads "PUSH BUTTON TO S 3. Go to the "Control Testing Menu". Select "D" for dry made press ENTER. 4. Air blank completed. 5. Calibration check completed. Test results 0. 100 6. Air blank completed. 7. Remove printed record. Attach the record to the completed. SIGNATURE	n on the simulator and allow temperature to reach 34°C ± TART" control test or "W" for wet control test. After selection isAC.
DPS Form Exh G-2 (Rev 05-01))

INTOXILYZER 8000 Location: JAIL

Serial Number: 80-003355 Core Version: 8105.48

05/19/2021 17:00:37

Standard Lot#: 35019100A1

Last Changed By: M. MALOY JR #281

QAS: M. MALOY JR #281 LAKE HAVASU CITY PD

Operator: M. MALOY JR #281

LAKE HAVASU CITY PD

Test	g/210L	Time
	* *	
Air Blank	0.000	17:01:12
0.100 Cal Check	0.100	17:01:33
Air Blank	0.000	17:02:02

Preventative Maintenance Performed -- Timer Reset

EXHIBIT G-4 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD QUALITY ASSURANCE PROCEDURE

QA SPECIALIST M. MALOY #281	AGENCY	LHCPS	
DATE 05-19-2021	TIME	1703	
INTOXILYZER SERIAL # 80-00 3355			
() 1. Display Reads "PUSH BUTTON TO START"			
DIAGNOSTIC TESTS () 1. Clock time check. () 2. Date check.			
OPERATIONAL TESTS () 1. Alcohol-free subject test result 0. OOO AC () 2. Error recognition logic system functioning. Not a Successfully Completed Test Sequence () 3. Proper sample recognition system. Not a Successfully Completed Test Sequence Deficient sample printed. () 4. Standard Calibration Check standard 0. 100 Instrument is operating properly and accurately. YES	ee printed ee printedAC. Result 0.	100 AC.	
COMMENTS			
	<u> </u>		
SIGNATURE Michael Maloy DPS Form Exh G-4 (Rev 05-01)	N #281		

INTOXILYZER 8000 Location: JAIL

Serial Number: 80-003355 Core Version: 8105.48

05/19/2021 17:03:44

Standard Lot#: 35019100A1
Last Changed By: M. MALOY JR #281

QAS: M. MALOY JR #281
LAKE HAVASU CITY PD

Operator: M. MALOY JR #281
LAKE HAVASU CITY PD

Subject: SQAP, TEST DOB: 01/01/2000

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	17:04:34
Diagnostic Test	Pass	17:05:09
Air Blank	0.000	17:05:37
0.100 Cal Check	0.100	17:05:57
Air Blank	0.000	17:06:27
Subject Test	0.000	17:06:48
Air Blank	ABT*	17:06:54
Air Blank	IPS**	17:07:03

^{*}Sequence Aborted

Not a Successfully Completed Test Sequence

^{**}Improper Sample

INTOXILYZER 8000 Location: JAIL

Serial Number: 80-003355 Core Version: 8105.48

05/19/2021 17:07:46

Standard Lot#: 35019100A1

Last Changed By: M. MALOY JR #281

QAS: M. MALOY JR #281

LAKE HAVASU CITY PD

Operator: M. MALOY JR #281

LAKE HAVASU CITY PD

Subject: SQAP, TEST DOB: 01/01/2000

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	17:08:40
Diagnostic Test	Pass	17:09:15
Air Blank	0.000	17:09:43
0.100 Cal Check	0.101	17:10:03
Air Blank	0.000	17:10:33
Subject Test	0.000*	17:13:40
Air Blank	0.000	17:14:08
Air Blank	0.000	17:14:35
Subject Test	XXX**	17:14:48
Air Blank	RFI***	17:15:00

^{*}Deficient Sample

Begin new deprivation period

Not a Successfully Completed Test Sequence

^{**}Invalid Sample

^{***}RFI Detect

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. MALOY # 781	AGENCY L H	2.PD
DATE 05-19-2021	пме17/	5
INTOXILYZER SERIAL # 80-00 3355	LOCATION	14
(1. Ensure that gas tank is attached to instrument and c	ontains a standard alcoho R	l concentration solution 0.100 AC
Pour a standard alcohol concentration solution simulator. Ensure that a tight seal has been made. 0.2°C	furn on the simulator and	d allow temperature to reach 34°C ±
 2. Intoxilyzer 8000 display reads "PUSH BUTTON T 3. Go to the "Control Testing Menu". Select "D" for made press ENTER. 	O START" ry control test or "W" fo	or wet control test. After selection is
 4. Air blank completed. 5. Calibration check completed. Test results 0. 10 6. Air blank completed. 	AC.	
(7. Remove printed record. Attach the record to the co	npleted checklist.	
SIGNATURE Muhael Mal	y g #281	
DPS Form Exh G-2 (Rev 05-01)		

INTOXILYZER 8000 Location: JAIL

Serial Number: 80-003355 Core Version: 8105.48

05/19/2021 17:15:55

Standard Lot#: 35019100A1

Last Changed By: M. MALOY JR #281

. В 46 ге кеменененен по сомышаным на настипация фагула

QAS: M. MALOY JR #281 LAKE HAVASU CITY PD

Operator: M. MALOY JR #281 LAKE HAVASU CITY PD

Test	g/210L	Time
Air Blank	0.000	17:16:32
0.100 Cal Check	0.100	17:16:53
Air Blank	0.000	17:17:22

Preventative Maintenance Performed Timer Reset