

To Whom It May Concern:

I hereby attest that Michael T. Maloy, Jr. is a Certified Intoxilyzer Quality Assurance Specialist for the Lake Havasu City Police Department.

I certify that the attached documentation of Standard Quality Assurance Procedures and/or Standard Calibration Check Procedure are full, true and correct copy of the original.

Mychael Malon J. 4781 Signature

STATE OF ARIZONA)
) ss
COUNTY OF MOHAVE)

Subscribed and sworn to before me this 15 day of September.


2021 by Ashley Rae Bonds

NOTARY PUBLIC

9-15-21

DATE

Commission expires: May 29, 2025



Area Code 928

Administration	855-4884	Fax #'s	
Business Office	855-1171	Administration 6	380-5430
Investigations	855-5775	Business Office 6	380-5431
Patrol	855-0515	Investigations/Patrol6	380-5432

E-mail: police@lhcaz.gov

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. MALOY #2BI AGENCY LNCPD
DATE 09-15-2021 TIME 1554
INTOXILYZER SERIAL # 80-001029 LOCATION LUCPO JAIL
(1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution OR
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
 2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START" 3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
4. Air blank completed. (5. Calibration check completed. Test results 0. AC. (6. Air blank completed.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE Michael Malong #281
DPS Form Exh G-2 (Rev 05-01)

Serial Number: 80-001029 Core Version: 8105.48

09/15/2021

15:54:34

Standard Lot#: 35019100A1

Last Changed By: K. TREBES #7259

QAS: M. MALOY JR #281 LAKE HAVASU CITY PD

Operator: M. MALOY JR #281

LAKE HAVASU CITY PD

Test	g/210L	Time
Air Blank	0.000	15:55:04
0.100 Cal Check	0.096	15:55:24
Air Blank	0.000	15:55:54

Preventative Maintenance Performed -- Timer Reset

EXHIBIT G-4 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD QUALITY ASSURANCE PROCEDURE

QA SPECIALIST M. MALOY #281 AGENCY LUCPD
DATE 09-15-2021 TIME 1557
INTOXILYZER SERIAL # 80-001029 LOCATION LUCPO JAIL
(1. Display Reads "PUSH BUTTON TO START"
DIACNOSTIC TESTS () \(\lambda \). Clock time check. () 2. Date check.
OPERATIONAL TESTS () 1. Alcohol-free subject test result 0. 00 AC. () 2. Error recognition logic system functioning. Not a Successfully Completed Test Sequence printed () 3. Proper sample recognition system. Not a Successfully Completed Test Sequence printed Deficient sample printed. () 4. Standard Calibration Check standard 0. 100 AC. Result 0. 097 AC. Instrument is operating properly and accurately. YES NO NO
COMMENTS
SIGNATURE_ Michael Maloygr #181
DPS Form Exh G-4 (Rev 05-01)

Serial Number: 80-001029 Core Version: 8105.48

09/15/2021

15:57:12

Standard Lot#: 35019100A1
Last Changed By: K. TREBES #7259

QAS: M. MALOY JR #281

LAKE HAVASU CITY PD

Operator: M. MALOY JR #281

LAKE HAVASU CITY PD

Subject: SQAP, TEST DOB: 01/01/2000

Sex: M

Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	15:58:03
Diagnostic Test	Pass	15:58:38
Air Blank	0.000	15:59:06
0.100 Cal Check	0.098	15:59:26
Air Blank	0.000	15:59:56
Subject Test	0.000	16:00:18
Air Blank	ABT*	16:00:25
Air Blank	IPS**	16:00:33

^{*}Sequence Aborted

^{**}Improper Sample

Serial Number: 80-001029 Core Version: 8105.48

09/15/2021 16:01:15

Standard Lot#: 35019100A1
Last Changed By: K. TREBES #7259

QAS: M. MALOY JR #281
LAKE HAVASU CITY PD

Operator: M. MALOY JR #281
LAKE HAVASU CITY PD

Subject: SQAP, TEST DOB: 01/01/2000

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	16:02:05
Diagnostic Test	Pass	16:02:41
Air Blank	0.000	16:03:08
0.100 Cal Check	0.098	16:03:29
Air Blank	0.000	16:03:58
Subject Test	0.000*	16:07:06
Air Blank	0.000	16:07:33
Air Blank	0.000	16:08:01
Subject Test	XXX**	16:08:15
Air Blank	RFI***	16:08:26

^{*}Deficient Sample

Begin new deprivation period

^{**}Invalid Sample

^{***}RFI Detect

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. MAWY #28 AGENCY LUCPD
DATE 09-15- 2021 TIME 1609
INTOXILYZER SERIAL # 30-001029 LOCATION LUCPO JAIL
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution OR
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C (2 Intoxilyzer 8000 display reads "PUSH BUTTON TO START"
3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
() 4. Air blank completed. () 5. Calibration check completed. Test results 0. 097 AC. () 6. Air blank completed.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE Michael Maloy # 281
DPS Form Exh G-2 (Rev 05-01)

Serial Number: 80-001029 Core Version: 8105.48

09/15/2021

16:09:11

Standard Lot#: 35019100A1

Last Changed By: K. TREBES #7259

QAS: M. MALOY JR #281 LAKE HAVASU CITY PD

Operator: M. MALOY JR #281

LAKE HAVASU CITY PD

Test	g/210L	Time
Air Blank	0.000	16:09:40
0.100 Cal Check	0.097	16:10:01
Air Blank	0.000	16:10:31

Preventative Maintenance Performed -- Timer Reset