

To Whom It May Concern:

I hereby attest that Michael T. Maloy, Jr. is a Certified Intoxilyzer Quality Assurance Specialist for the Lake Havasu City Police Department.

I certify that the attached documentation of Standard Quality Assurance Procedures and/or Standard Calibration Check Procedure are full, true and correct copy of the original.

Area Code 928

Administration	855-4884	Fax #'s	Emergency 9-1-1
Business Office	855-1171	Administration 680-5430	Non-Emergency Dispatch/ 855-4111
Investigations		Business Office 680-5431	Havasu Silent Witness 854-TIPS
Patrol	855-0515	Investigations/Patrol 680-5432	

E-mail: police@lhcaz.gov

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M- MALDY #281 AGENCY LULPD
DATE 07-19-2020 TIME 0711
INTOXILYZER SERIAL # 80-001873 LOCATION LICPO JAIL
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution OR
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START" 3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
 4. Air blank completed. 5. Calibration check completed. Test results 0. <u>D9 B</u> AC. 6. Air blank completed. 7. Remove printed record. Attach the record to the completed checklist.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE Michael Malon #281
DPS Form Exh G-2 (Rev 05-01)

INTOXILYZER 8000 Location: LHCPD

Serial Number: 80-001873 Core Version: 8105.48

07/19/2020 07:11:59

Standard Lot#: 35019100A1

Last Changed By: M. MALOY JR #281

QAS: M. MALOY JR #281 LAKE HAVASU CITY PD

Operator: M. MALOY JR #281

LAKE HAVASU CITY PD

Test	g/210L	Time
Air Blank	0.000	07:12:31
0.100 Cal Check	0.098	07:12:51
Air Blank	0.000	07:13:21

Preventative Maintenance
Performed -- Timer Reset

$EXHIBIT~G-4 \\ THIS REPORT PREPARED PURSUANT~TO~DUTY~IMPOSED~BY~A.A.C.~R13-10-104~(A) \\$

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD QUALITY ASSURANCE PROCEDURE

QA SPECIALIST M- MALDY # 281	AGENCY	LHLPD	
DATE 07-19- 2020	TIME0?	15	
INTOXILYZER SERIAL# 80 - 601873	LOCATION	LMCPO	JAIL
() 1. Display Reads "PUSH BUTTON TO START"			
DIAGNOSTIC TESTS () 1. Clock time check. () 2. Date check.			
OPERATIONAL TESTS () 1. Alcohol-free subject test result 0			
SIGNATURE Michael Malaygr	#281		
DPS Form Exh G-4 (Rev 05-01)			

INTOXILYZER 8000 Location: LHCPD

Serial Number: 80-001873 Core Version: 8105.48

07/19/2020

07:15:32

Standard Lot#: 35019100A1
Last Changed By: M. MALOY JR #281

QAS: M. MALOY JR #281
LAKE HAVASU CITY PD

Operator: M. MALOY JR #281
LAKE HAVASU CITY PD

Subject: SQAP, TEST DOB: 01/01/2000

Sex: M

Weight: 200

15 Minute Deprivation Period? Yes

		•
Test	g/210L	Time
Air Blank	0.000	07:16:45
Diagnostic Test	Pass	07:17:20
Air Blank	0.000	07:17:48
0.100 Cal Check	0.099	07:18:08
Air Blank	0.000	07:18:38
Subject Test	0.000	07:19:03
Air Blank	ABT*	07:19:10
Air Blank	IPS**	07:19:18

^{*}Sequence Aborted

^{**}Improper Sample

INTOXILYZER 8000 Location: LHCPD

Serial Number: 80-001873 Core Version: 8105.48

07/19/2020

07:20:22

Standard Lot#: 35019100A1
Last Changed By: M. MALOY JR #281

QAS: M. MALOY JR #281
LAKE HAVASU CITY PD

Operator: M. MALOY JR #281
LAKE HAVASU CITY PD

Subject: SQAP, TEST DOB: 01/01/2000

Sex: M

Weight: 200

15 Minute Deprivation Period? Yes

g/210L	Time
0.000	07:21:11
Pass	07:21:46
0.000	07:22:14
0.098	07:22:34
0.000	07:23:04
0.000*	07:26:11
0.000	07:26:39
0.000	07:27:06
XXX**	07:27:24
RFI***	07:27:32
	0.000 Pass 0.000 0.098 0.000 0.000* 0.000 0.000 XXX**

^{*}Deficient Sample

Begin new deprivation period

***RFI Detect

^{**}Invalid Sample

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. MALDY #281 AGENCY LUCPD
DATE 67-19-2020 TIME 0730
INTOXILYZER SERIAL # 80-001873 LOCATION LNCPD JAIL
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution OR
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
 Intoxilyzer 8000 display reads "PUSH BUTTON TO START" Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
4. Air blank completed. 5. Calibration check completed. Test results 0. <u>099</u> AC. 6. Air blank completed.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE Michael Malon J #281
DPS Form Exh G-2 (Rev 05-01)

INTOXILYZER 8000 Location: LHCPD

Serial Number: 80-001873 Core Version: 8105.48

07/19/2020

07:30:16

Standard Lot#: 35019100A1

Last Changed By: M. MALOY JR #281

QAS: M. MALOY JR #281 LAKE HAVASU CITY PD ______

Operator: M. MALOY JR #281

LAKE HAVASU CITY PD ______

Test	g/210L	Time
Air Blank 0.100 Cal Check Air Blank	0.000 0.099 0.000	07:30:47 07:31:07 07:31:37

Preventative Maintenance Performed -- Timer Reset