

EXHIBIT G-2  
THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY  
STANDARD QUALITY ASSURANCE PROCEDURES  
INTOXILYZER MODEL 8000  
STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST J SONDRA 187 AGENCY LNC PD  
DATE 4/23/17 TIME 1430  
INTOXILYZER SERIAL # 80-003356 LOCATION MAIN TRIL

- (✓) 1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution 100 AC.  
OR  
Pour a standard alcohol concentration solution \_\_\_\_\_ AC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach  $34^{\circ}\text{C} \pm 0.2^{\circ}\text{C}$
- (✓) 2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START"
- (✓) 3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
- (✓) 4. Air blank completed.
- (✓) 5. Calibration check completed. Test results 0.096 AC.
- (✓) 6. Air blank completed.
- (✓) 7. Remove printed record. Attach the record to the completed checklist.

SIGNATURE Sondra 187

DPS Form Exh G-2 (Rev 05-01)

\* ONLY COMPLETED 30-DAY G-2 DUE TO BEING GONE ON TRAINING  
\* WILL DO FULL G-2, G-4, G-2 ON 5/23/17

2/15

INTOXILYZER 8000  
Location: MAIN JAIL  
Serial Number: 80-003356  
Core Version: 8105.48  
04/23/2017

14:30:25

-----  
Standard Lot#: 22315100A1  
Last Changed By: J. SONDRON #187  
-----

QAS: J. SONDRON #187  
LAKE HAVASU CITY PD  
-----

Operator: J. SONDRON #187  
LAKE HAVASU CITY PD  
-----

Test	g/210L	Time
Air Blank	0.000	14:31:09
0.100 Cal Check	0.096	14:31:30
Air Blank	0.000	14:32:00

Preventative Maintenance  
Performed -- Timer Reset