

To Whom It May Concern:

Commission expires:

I hereby attest that Michael T. Maloy, Jr. is a Certified Intoxilyzer Quality Assurance Specialist for the Lake Havasu City Police Department.

I certify that the attached documentation of Standard Quality Assurance Procedures and/or Standard Calibration Check Procedure are full, true and correct copy of the original.

STATE OF ARIZONA
) ss

COUNTY OF MOHAVE
)

Subscribed and sworn to before me this 18th day of March.

Zoz I by Michael T. Walou Jr

NOTARY PUBLIC

3-18-21

DATE

LORI SCHNEPF
Notary Public - Arizona
Mohave County
Commission # 558867
My Comm. Expires Feb 26, 2023

Area Code 928

 Administration
 855-4884
 Fax #'s
 Emergency
 9-1-1

 Business Office
 855-1171
 Administration
 680-5430
 Non-Emergency Dispatch/
 855-4111

 Investigations
 855-5775
 Business Office
 680-5431
 Havasu Silent Witness
 854-TIPS

 Patrol
 855-0515
 Investigations/Patrol
 680-5432
 680-5432

E-mail: police@Ihcaz.gov

### EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

#### ARIZONA DEPARTMENT OF PUBLIC SAFETY

### STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

#### STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. MALOY # 281	AGENCYL	ncpo
DATE 03-18-2021	TIME	0704
INTOXILYZER SERIAL # 80-003355	LOCATION	JAIL
( X 1. Ensure that gas tank is attached to instrument and	contains a standard	d alcohol concentration solution O.100 AC.
Pour a standard alcohol concentration solution simulator. Ensure that a tight seal has been made. 0.2°C  2. Intoxilyzer 8000 display reads "PUSH BUTTON" of the "Control Testing Menu". Select "D" for made press ENTER.  4. Air blank completed.  5. Calibration check completed. Test results 0. 10  6. Air blank completed.  7. Remove printed record. Attach the record to the completed.	Turn on the simu  FO START <sup>**</sup> dry control test of	lator and allow temperature to reach $34^{\circ}\text{C} \pm$ r "W" for wet control test. After selection is
SIGNATURE Michael Maly	Jr # UB1	
DPS Form Exh G-2 (Rev 05-01)		

Serial Number: 80-003355 Core Version: 8105.48

03/18/2021

07:04:31

------

Standard Lot#: 35019100A1

Last Changed By: M. MALOY JR #281

-----

QAS: M. MALOY JR #281 LAKE HAVASU CITY PD

\*\*\*\*\*

Operator: M. MALOY JR #281

LAKE HAVASU CITY PD

------

Test	g/210L	Time
Air Blank	0.000	07:05:13
0.100 Cal Check	0.101	07:05:34
Air Blank	0.000	07:06:04

Preventative Maintenance Performed -- Timer Reset

# ${\bf EXHIBIT~G-4}\\ {\bf THIS~REPORT~PREPARED~PURSUANT~TO~DUTY~IMPOSED~BY~A.A.C.~R13-10-104~(A)}$

#### ARIZONA DEPARTMENT OF PUBLIC SAFETY

### STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

### STANDARD QUALITY ASSURANCE PROCEDURE

QA SPECIALIST M. MALOY # CBI AGENCY LHCPD
DATE 03-18-2021 TIME 070b
INTOXILYZER SERIAL # 80-003355 LOCATION JAIL
( 🗸 1. Display Reads "PUSH BUTTON TO START"
DIAGNOSTIC TESTS  ( ) 1. Clock time check. ( ) 2. Date check.
OPERATIONAL TESTS  ( ) 1. Alcohol-free subject test result 0. DOD AC.  ( ) 2. Error recognition logic system functioning.  Not a Successfully Completed Test Sequence printed  ( ) 3. Proper sample recognition system.  Not a Successfully Completed Test Sequence printed  Deficient sample printed.  ( ) 4. Standard Calibration Check standard 0. DOD AC.
Instrument is operating properly and accurately. YES NO
COMMENTS
×
SIGNATURE_MichaelMalygy #281
DPS Form Exh G-4 (Rev 05-01)

Serial Number: 80-003355 Core Version: 8105.48

03/18/2021

07:06:49

Standard Lot#: 35019100A1 Last Changed By: M. MALOY JR	#281
QAS: M. MALOY JR LAKE HAVASU CITY PD	#281
Operator: M. MALOY JR LAKE HAVASU CITY PD	#281

Subject: SQAP, TEST DOB: 01/01/2000

Sex: M

Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	07:07:47
Diagnostic Test	Pass	07:08:22
Air Blank	0.000	07:08:50
0.100 Cal Check	0.100	07:09:11
Air Blank	0.000	07:09:40
Subject Test	0.000	07:10:12
Air Blank	ABT*	07:10:18
Air Blank	IPS**	07:10:26

<sup>\*</sup>Sequence Aborted
\*\*Improper Sample

Serial Number: 80-003355 Core Version: 8105.48

03/18/2021

07:11:25

Standard Lot#: 35019100A1
Last Changed By: M. MALOY JR #281

QAS: M. MALOY JR #281
LAKE HAVASU CITY PD

Operator: M. MALOY JR #281
LAKE HAVASU CITY PD

Subject: SQAP, TEST DOB: 01/01/2000

Sex: M

Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	07:12:17
Diagnostic Test	Pass	07:12:52
Air Blank	0.000	07:13:19
0.100 Cal Check	0.101	07:13:40
Air Blank	0.000	07:14:10
Subject Test	0.000*	07:17:17
Air Blank	0.000	07:17:44
Air Blank	0.000	07:18:12
Subject Test	XXX**	07:18:26
Air Blank	RFI***	07:18:38

<sup>\*</sup>Deficient Sample

Begin new deprivation period

Not a Successfully Completed Test Sequence

<sup>\*\*</sup>Invalid Sample

<sup>\*\*\*</sup>RFI Detect

## EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

#### ARIZONA DEPARTMENT OF PUBLIC SAFETY

### STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

#### STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. MALOY #281	AGENCY	LHCPD
DATE 03-18-2021	TIME	0719
INTOXILYZER SERIAL# 80-60 3355	LOCATION_	JAIL ,
( 1. Ensure that gas tank is attached to instrument and c	contains a standa OR	ard alcohol concentration solutionAC.
Pour a standard alcohol concentration solution simulator. Ensure that a tight seal has been made. 0.2°C  2. Intoxilyzer 8000 display reads "PUSH BUTTON T 3. Go to the "Control Testing Menu". Select "D" for made press ENTER.  4. Air blank completed. 5. Calibration check completed. Test results 0. 100 6. Air blank completed. 7. Remove printed record. Attach the record to the control of the contr	Turn on the sime of START" dry control test	aulator and allow temperature to reach $34^{\circ}\text{C} \pm$ or "W" for wet control test. After selection is
SIGNATURE Michael Mak	ng #	281
DPS Form Exh G-2 (Rev 05-01)		

Serial Number: 80-003355 Core Version: 8105.48

03/18/2021 07:19:28

-----

Standard Lot#: 35019100A1

Last Changed By: M. MALOY JR #281

------

QAS: M. MALOY JR #281 LAKE HAVASU CITY PD

Operator: M. MALOY JR #281

LAKE HAVASU CITY PD

------

Test	g/210L	Time
Air Blank	0.000	07:19:59
0.100 Cal Check	0.100	07:20:20
Air Blank	0.000	07:20:49

Preventative Maintenance Performed -- Timer Reset